

**Materialprüfungsamt Nordrhein-Westfalen**

Prüfen • Überwachen • Zertifizieren

**Certificate of constancy of performance****0432-CPR-00007-14**

(Version: 01)

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

**Emergency exit devices ASSA ABLOY "Series x09N / x19N"**

Emergency exit devices operated by a lever handle or push pad, for use on escape routes  
as detailed and classified on appendix 2,

placed on the market under the name or trade mark of

**ASSA ABLOY Sicherheitstechnik GmbH****Bildstockstr. 20****72458 Albstadt****Deutschland**

and produced in the manufacturing plant(s)

**DO 22.0**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standard(s)


**EN 179: 2008**

under **system 1** for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

**constancy of performance of the construction product.**

This certificate was first issued on 28.01.2016 and will remain valid until 28.01.2021 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Dortmund, 28.01.2016

  
Dipl.-Ing. H. Jansen  
Certification Body

This Certificate consists of 1 page and 3 annex

The original of this document was issued in German language.  
In case of doubt only the German version is valid.



## Emergency exit devices ASSA ABLOY „Series x09N / x19N”

### Manufacturing plants

Product	Manufacturing plants
locks	ASSA ABLOY Sicherheitstechnik GmbH Werk Albstadt Bildstockstr. 20 D-72458 Albstadt DO 22.0
handles	<p>FSB Franz Schneider Brakel GmbH Nieheimer Straße 38 D-33034 Brakel DO 20.3</p> <p>-----</p> <p>ASSA ABLOY Sicherheitstechnik GmbH Werk Berlin Goerzallee 299 D-14167 Berlin DO 20.15</p> <p>-----</p> <p>HEWI Heinrich Wilke GmbH Prof.-Bier Str.1-5 D-34442 Bad Arolsen DO 20.13</p> <p>-----</p> <p>ASSA ABLOY Sicherheitstechnik GmbH Werk Albstadt Bildstockstr. 20 D-72458 Albstadt DO 22.0</p> <p>-----</p> <p>HOPPE AG Havelstraße 31 D-35620 Stadtallendorf DO 20.5, DO 20.7, DO 20.20</p> <p>-----</p> <p>Vieler Architectural Hardware GmbH Zur Helle 28 58638 Iserlohn Germany DO 20.12</p>



# Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

Glutz AG  
Segetzstrasse 13  
CH-4502 Solothurn  
Schweiz  
DO 20.21

-----  
ASSA ABLOY S.p. A./ Milano Unit  
Via Concordia 16  
I – 20838 Renate (MB)  
DO 2.18

-----  
HAFI Beschläge GmbH  
Weissinger Straße 16  
D – 89275 Elchingen

Emergency exit devices according to DIN EN 179 for single leaf doors

## Emergency exit devices ASSA ABLOY „Series x09N / x19N”

locks

Item no.	VS-type	Function	Backset	Distance	Forend width	Classification	cmd
309NB0 <sup>b</sup>	B/D	Va	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
309NE0 <sup>b</sup>	B/D	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
509NE0 <sup>b</sup>	B/D	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
809NE0 <sup>b</sup>	B/D	II	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
319NB0 <sup>b</sup>	B/D	Va	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
319NE0 <sup>b</sup>	B/D	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
519NE0 <sup>b</sup>	B/D	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
819NE0 <sup>b</sup>	B/D	II	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
309NB2 <sup>b</sup>	B/D	Va	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
309NE2 <sup>b</sup>	B/D	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
509NE2 <sup>b</sup>	B/D	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
809NE2 <sup>b</sup>	B/D	II	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
319NB2 <sup>b</sup>	B/D	Va	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
319NE2 <sup>b</sup>	B/D	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
519NE2 <sup>b</sup>	B/D	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9
819NE2 <sup>b</sup>	B/D	II	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A B/D	1-9

Max. door leaf weight: 300 kg

Max. door leaf width: 1500 mm

Max door leaf height: 2500 mm

b) all kinds of cylinders do not have influence on the escape function of the lock.

cmb: indicates the valid combination between the lock and the handle. See also the table for handle, annex 2.

Function I: one-piece follower, constantly working escape door function.  
Inside opening is always possible over the handle. Outside opening is possible with a key.

Function II: splitted follower, constantly working escape door function from the inside.  
Opening is always possible over the interior handle from the inside. The external handle is electronic coupled in or out. A special handle with a splitted spindle is needed.

# Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

function Va: splitted follower, constantly working escape door function from the inside. The external handle is constantly coupled in or out. Opening is always possible over the interior handle from the inside. The external handle will be coupled or uncoupled by operating the key.

VS-type A: lock for a single or a double leaf door: active or inactive leaf.

VS-type B: lock for a single leaf door.

VS-type C: lock for a double leaf door: only inactive leaf.

VS-type D: Lock for inside opening single leaf doors

Remark: In agreement with the terms of the German building regulation legislation, a lock of VS-type B according to DIN EN 179 (lock for single leaf doors) can be used also in the active leaf of a double leaf door, if:

- a) the inactive leaf catch is secured against maloperation, and
- b) the passage width of the active leaf is sufficient as escape route width.

## handles

No.	Manufacturer	Code
1	ASSA ABLOY Sicherheitstechnik GmbH Werk Berlin	DO 20.15.01 DO 20.15.02
2	FSB	DO 20.3.01 DO 20.3.02
3	HEWI	DO 20.13.01 DO 20.13.02
4	ASSA ABLOY Sicherheitstechnik GmbH Werk Albstadt	DO 22.0.01 DO 22.0.02
5	HOPPE	DO 20.x.01 DO 20.x.02
6	Vieler	DO 20.12.01 DO 20.12.02
7	Glutz	DO 20.21.01 DO 20.21.02
8	HAFI	
9	ASSA ABLOY S.p. A./ Milano Unit	DO 2.18



## Alternative and additional equipment

### **Bolt switching contact**

Type 031308

Type 031309

### **Bolt extension**

Type 819 ZBV

Only in conjunction with locks 819NE2, 519NE2, 319NE2, 319NB2, 819NE0, 519NE0, 319NE0 and 319NBO possible.

### **Intergrated additional Lock**

Latch 807.10 with emergency electric strike modell 331/332