

Materialprüfungsamt Nordrhein-Westfalen
Prüfen • Überwachen • Zertifizieren

Certificate of constancy of performance
0432-CPR-00007-15
(Version: 02)

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Panic exit devices ASSA ABLOY "Series x09N / x19N"

Panic exit devices operated by a horizontal bar, for use on escape routes
as detailed and classified on appendix 2,

placed on the market under the name or trade mark of

ASSA ABLOY Sicherheitstechnik GmbH
Bildstockstr. 20
72458 Albstadt
Deutschland

and produced in the manufacturing plant(s)

DO 22.0

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standard(s)

EN 1125: 2008

under **system 1** for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 28.01.2016 and will remain valid until 28.01.2021 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Dortmund, 16.02.2016




Dipl.-Ing. H. Jansen
Certification Body

This Certificate consists of 1 page and 3 annexes.

This Certificate replaces the Certificate no. 0432-CPR-00007-15 dated 28.01.2016, Version 01.

The original of this document was issued in German language.
In case of doubt only the German version is valid.



Panic exit devices ASSA ABLOY „Series x09N / x19N”**Manufacturing plants**

Product	Manufacturing plants
locks	ASSA ABLOY Sicherheitstechnik GmbH Werk Albstadt Bildstockstr. 20 D-72458 Albstadt DO 22.0
bars	ASSA ABLOY Sicherheitstechnik GmbH Werk Albstadt Bildstockstr. 20 D-72458 Albstadt DO 22.0

Panic exit devices according to DIN EN 1125 for single leaf doors

Panic exit devices ASSA ABLOY „Series x09N / x19N”

locks

Item no.	VS-type	Function	Backset	Distance	Forend width	Classification	cmd
309NB0 ^b	B	Va	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
309NE0 ^b	B	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
509NE0 ^b	B	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
809NE0 ^b	B	II	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
319NB0 ^b	B	Va	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
319NE0 ^b	B	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
519NE0 ^b	B	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
819NE0 ^b	B	II	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
309NB2 ^b	B	Va	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
309NE2 ^b	B	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
509NE2 ^b	B	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
809NE2 ^b	B	II	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
319NB2 ^b	B	Va	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
319NE2 ^b	B	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
519NE2 ^b	B	I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4
819NE2 ^b	B	II	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3 7 7 B 1 3 2 2 A/B B	1-4

Max. door leaf weight: 300 kg

Max. door leaf width: 1500 mm

Max door leaf height: 2500 mm

b) all kinds of cylinders do not have influence on the escape function of the lock.
cmb: indicates the valid combination between the lock and the handle.

Function I: one-piece follower, constantly working escape door function.
Inside opening is always possible over the handle. Outside opening is possible with a key.

Function II: splitted follower, constantly working escape door function from the inside.
Opening is always possible over the interior handle from the inside. The external handle is electronic coupled in or out. A special handle with a splitted spindle is needed.

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

function Va: splitted follower, constantly working escape door function from the inside. Opening is always possible over the interior handle from the inside. The external handle will be coupled or uncoupled by operating the key.

VS-type A: lock for a single or a double leaf door: active or inactive leaf.

VS-type B: lock for a single leaf door.

VS-type C: lock for a double leaf door: only inactive leaf.

Remark: In agreement with the terms of the German building regulation legislation, a lock of VS-type B according to DIN EN 1125 (lock for single leaf doors) can be used also in the active leaf of a double leaf door, if:

- a) the inactive leaf catch is secured against maloperation, and
- b) the passage width of the active leaf is sufficient as escape route width.

bars

No.	Manufacturer	Type	Code
1	ASSA ABLOY Sicherheitstechnik GmbH	N2500	DO 22.0
2	ASSA ABLOY Sicherheitstechnik GmbH	N2600	DO 22.0
3	ASSA ABLOY Sicherheitstechnik GmbH	N2000	DO 22.0
4	ASSA ABLOY Sicherheitstechnik GmbH	N2100	DO 22.0



Alternative and additional equipment

Bolt switching contact

Type 031308

Type 031309

Bolt extension

Type 819 ZBV

Only in conjunction with locks 819NE2, 519NE2, 319NE2, 319NB2, 819NE0, 519NE0, 319NE0 and 319NBO possible.

Intergrated additional Lock

Latch 807.10 with emergency electric strike model 331/332