

Escape route technology from effeff



EXITalarm
Security at emergency exits



Model 7411

ASSA ABLOY, the global leader
in door opening solutions

EXITalarm

Security at emergency exits



Alarm if an emergency exit is misused

EXITalarm is an emergency exit door alarm which detects when the door handle is turning. It emits an audible and optical signal if the handle on an escape route door is used. Thanks to its precise position, it provides a highly effective deterrent against misuse of emergency exits.

EXITalarm is an ideal product for a simple, easy-to-install retrofit since it requires no wiring and is powered by a 9 V battery.

Overview of advantages:

- Emergency exits easily secured
- Alarm if emergency exit is misused: optical and audible signal triggered if door handle is turned
- Visible deterrent against unauthorised use of the door
- Scaring Pre Alarm if handle is turned slightly
- Surveillance function which can be switched off
- Alarm activated or reset via Euro Profile or Swiss round profile cylinder
- Risk of fingers getting caught minimised: lever folds away completely when door handle is used
- Suitable as a retrofit for existing doors
- Can be combined with most EN 179 emergency exit devices – please follow safety instructions
- No wiring necessary as device is powered by a 9 V battery
- Lever can be set in two directions - height- and horizontally adjustable
- Flexibly adapted for installation in a wide range of door installation types and locations
- Easily mounted onto different surfaces: screw attachment or glued into position on glass doors, for example

Financial loss due to misuse of escape routes



EXITalarm

Operating modes

Surveillance function



Surveillance in the door handle provides a greater deterrent against misuse of emergency exits. The position of the lever clearly indicates that the alarm will be triggered immediately if the handle is used. This system ensures that the emergency exit is protected simply and effectively.

Authorised door usage



The locking cylinder fitted into the lock is used for, authorised opening of the door from both sides. The lock must feature a transmission function if you wish to incorporate authorised use. The door handle is thus still monitored without inconveniencing the user.

Deactivating the surveillance function



The surveillance alarm can be deactivated by the profile cylinder. The surveillance lever is secured in the lower position. The door can now be opened using the door handle without triggering the alarm.

Warning alarm



Triggered when the handle is used, a warning alarm ensures a more effective deterrent against misuse of an emergency exit. If the surveillance handle is opened slightly, an audible alarm is emitted, which will automatically stop the handle is released.

Emergency opening



The door can be opened in an emergency by using the door handle. If opened, the surveillance lever is activated and an audible alarm is sounded, which can only be reset using the integrated locking cylinder. The surveillance lever swings downwards if the door is opened, thus also giving visual indication that the alarm has been triggered.

EXITalarm

Universal installation



Metal frame door with glass insert: mounted on glass

Thanks to the surveillance lever's horizontal and vertical adjustment, EXITalarm can be easily adapted to the structural conditions of any door. In addition to universal right-hand/left-hand positioning, the device also offers stepped angular adjustment to compensate for different mounting surface levels. Featuring an adhesive foil as standard, the mounting plate also provides attachment suitable for surfaces such as glass, an alternative to fixing by screws. With EXITalarm, the emphasis is on easy, versatile installation with fitting accessories kept to a minimum.

Included in supplied package

- EXITalarm, attached using screws or adhesive foil
- Fixing screws
- Adhesive foil, pre-attached to EXITalarm
- Dressing strip to cover gluing surface on opposite side of glass.
- 9 V monobloc battery
- Locking cylinder with 3 keys Can be exchanged on site with a profile half cylinder, 30 mm long, locking bit position facing upwards



Mounted on wooden and steel doors



Metal frame door with glass insert: mounted on frame



ASSA ABLOY is the
global leader in door
opening solutions,
dedicated to satisfying
end-user needs for
security, safety and
convenience.



ASSA ABLOY

ASSA ABLOY
Sicherheitstechnik GmbH

Bildstockstrasse 20
72458 Albstadt
GERMANY
Tel. +49 7431 123-700
Fax: +49 7431 123-258
albstadt@assaabloy.de

www.assaabloy.de