

Materialprüfungsamt Nordrhein-Westfalen

Prüfen • Überwachen • Zertifizieren

**Certificate of Constancy of performance
0432-CPR-00007-01**

Version 02

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Emergency exit devices effeff

emergency exit devices operated by a lever handle for single leaf doors
as detailed and classified on annex 2,

produced by or for

ASSA ABLOY Sicherheitstechnik GmbH

Bildstockstr.20
D - 72458 Albstadt

and produced in the manufacturing plant(s)

see annex 1


This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in annex ZA of the standard(s)

EN 179:2008under **system 1** are applied and that**the product fulfils (products fulfil) all the prescribed
requirements set out above.**

This certificate was first issued on 15.09.2015 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly, or latest on 15.09.2020.



Dortmund, 13.10.2015


Dipl. -Ing. H. Jansen
Head of Certification Body

This Certificate consists of 1 page and 3 annex(es).

This Certificate replaces the Certificate no. 0432-CPR-00007-01 dated
15.09.2015.



The original of this document was issued in German language. In case of doubt only the

German version is valid.

Emergency exit devices effeff

Manufacturing plants

Product	Manufacturing plants
locks	<p>ASSA ABLOY Sicherheitstechnik GmbH Werk Albstadt Bildstockstr. 20 D-72458 Albstadt DO 22.0</p> <p>-----</p> <p>Abloy Oy Wahlforssinkatu 20 FIN-80101 Joensuu Finland DO 6.7</p>
handles	<p>FSB Franz Schneider Brakel GmbH Nieheimer Straße 38 D-33034 Brakel DO 20.3</p> <p>-----</p> <p>ASSA ABLOY Sicherheitstechnik GmbH Werk Berlin Goerzallee 299 D-14167 Berlin DO 20.15</p> <p>-----</p> <p>HEWI Heinrich Wilke GmbH Prof.-Bier Str.1-5 D-34442 Bad Arolsen DO 20.13</p> <p>-----</p> <p>ASSA ABLOY Sicherheitstechnik GmbH Werk Albstadt Bildstockstr. 20 D-72458 Albstadt DO 22.0</p> <p>-----</p> <p>HOPPE AG Havelstraße 31 D-35620 Stadtallendorf DO 20.5, DO 20.7, DO 20.20</p> <p>-----</p>

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

Vieler Architectural Hardware GmbH
Zur Helle 28
58638 Iserlohn
Germany
DO 20.12

Glutz AG
Segetzstrasse 13
CH-4502 Solothurn
Schweiz
DO 20.21

HAFI Beschläge GmbH
Weissinger Straße 16
D-89275 Elchingen
DO 20.32

HAFI Beschläge GmbH
Weissinger Straße 16
D-89275 Elchingen
DO 20.32

ASSA ABLOY S.p. A./ Milano Unit
Via Concordia 16
I – 20838 Renate (MB)
DO 2.18

ECO Schulte GmbH & Co. KG
Iserlohnerlandstraße 117
D – 58706 Menden
DO 20.1

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

Emergency exit devices according to DIN EN 179 for single leaf doors

Emergency exit devices effeff

locks

Item No.	VS-type	Function	Backset	Distance	Forend width	Classification										Drk
						3	7	6	B	1	3	5	2	A	B/D	
309-B ^{b)}	B/D	Function Va	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3	7	6	B	1	3	5	2	A	B/D	1-9
309 MB ^{b)}	B/D	Function Va	60, 65 mm	72 mm PZ 74 mm RZ	≥ 20 mm	3	7	6	B	1	3	5	2	A	B/D	1-9
809 M ^{b)}	B/D	Function II	60, 65 mm	72 mm PZ 74 mm RZ	≥ 20 mm	3	7	6	B	1	3	5	2	A	B/D	1-9
319E-B ^{b)}	B/D	Function Va	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3	7	6	B	1	3	5	2	A	B/D	1-9
319 E ^{b)}	B/D	Function I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3	7	6	B	1	3	5	2	A	B/D	1-9
519 E ^{b)}	B/D	Function I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3	7	6	B	1	3	5	2	A	B/D	1-9
509E ^{b)}	B/D	Function I	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3	7	6	B	1	3	5	2	A	B/D	1-9
809 ^{b)}	B/D	Function II	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3	7	6	B	1	3	5	2	A	B/D	1-9
819 ^{b)}	B/D	Function II	35 bis 80 mm	92 mm PZ 94 mm RZ	≥ 20 mm	3	7	6	B	1	3	5	2	A	B/D	1-9

b) All kinds of cylinders do not have influence on the escape function of the lock.

drk: indicates the valid combination between the lock and the handle.

function I: constantly working escape door function. Opening is always possible over the handle.

function II: splitted follower, constantly working escape door function from the inside. Opening is always possible over the interior handle from the inside. The external handle will be coupled by an electronically device.

function Va: splitted follower, constantly working escape door function from the inside. Opening is always possible over the interior handle from the inside. The external handle will be coupled or uncoupled by operating the key.

VS-type A: lock for a single or a double leaf door: active or inactive leaf.

VS-type B: lock for a single leaf door.

VS-type C: lock for a double leaf door: only inactive leaf.

VS-type D: Lock for inside opening single leaf doors

Remark: In agreement with the terms of the German building regulation legislation, a lock of VS-type A according to

DIN EN 179 (lock for single leaf doors) can be used also in the active leaf of a double leaf door, if:

a) the inactive leaf catch is secured against maloperation, and

b) the passage width of the active leaf is sufficient as escape route width.

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

Handles

No.	Manufacturer	Coding
1	ASSA ABLOY Sicherheitstechnik GmbH Werk Berlin	DO 20.15.01 DO 20.15.02
2	FSB	DO 20.3.01 DO 20.3.02
3	HEWI	DO 20.13.01 DO 20.13.02
4	ASSA ABLOY Sicherheitstechnik GmbH Werk Albstadt	DO 22.0.01 DO 22.0.02
5	HOPPE	DO 20.x.01 DO 20.x.02
6	Vieler	DO 20.12.01 DO 20.12.02
7	Glutz	DO 20.21.01 DO 20.21.02
8	HAFI	DO 20.32.01 DO 20.32.02
9	ASSA ABLOY S.p.A./ Milano Unit	DO 2.18
10	ECO	DO 20.1



Alternative and additional equipment

Bolt switching contact

Type 031308

Type 031309

Bolt extension

Type 819 ZBV

Only in conjunction with locks type 819 E, 519 E, 319 E and 319 EB possible.

Intergrated additional Lock

Latch 807.10 with emergency electric strike modell 331/332