

Nr.: DoP-819E.01

**1. Unique identification code of the product-type:**

Panic exit devices, for use on escape routes according to EN 1125:2008  
Lock model 819E in all variants

**2. Intended use/es:**

Panic exit devices operated by a horizontal bar, for use on escape routes according to EN 1125:2008

**3. Manufacturer:**

ASSA ABLOY  
Sicherheitstechnik GmbH  
Bildstockstraße 20  
72458 Albstadt  
DEUTSCHLAND

**4. Authorised representative:**

N.N

**5. System/s of AVCP:**

System 1 according to EN 1125:2008

**6.a Harmonised standard:**

Notified body	Harmonised standard	Certificat of Constancy of performance
MPA NRW, Marsbruchstraße 186; D-44287 Dortmund, Kennung:0432	EN 1125:2008	0432-CPR-00007-02 (V02

The product is covered by other EC-directives:  
N.N

**6.b European Assessment Document:**

N.N

## 7. Declared performance/s:

Declared performance according to EN 1125:2008

Requirement / characteristic	Section	Performance	Harmonised standard
Ability to release (for doors on escape routes)	4.2.1	Threshold values: passed	EN 1125:2008
Durability of ability to release against aging and degradation (for doors on escape routes)	4.2.1	Threshold values: passed	EN 1125:2008
Self closing ability C (for fire/smoke doors on escape routes)	4.2.1	Threshold values: passed	EN 1125:2008
Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes)	4.2.1	Threshold values: passed	EN 1125:2008
Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes)	4.2.1	Fire test: passed	EN 1125:2008
Control of Dangerous substances	4.1.25	The materials used in the product do not contain or release any dangerous Substances in excess of the maximum levels specified in existing European Material standards or any national regulations.	EN 1125:2008

Classification code according to EN 1125:2008

Position	1	2	3	4	5	6	7	8	9	10	11
Section	7.1	7.2	7.3	7.4	7.5	7.6	7.7	7.8	7.9	7.10	
Class	3	7	6	B	1	3	2	W	A	B	

Pos	Ess. characteristics	Class – Performance	
1	Application class	3	High frequency use where there is little incentive to exercise care
2	Durability		test cycles
		6 7	100.000 200.000
3	Door mass		door mass [kg]
		5	≤ 100
		6 7	≤ 200 > 200
4	Fire / smoke protection		use
		0 A B	Not approved for use on fire / smoke door assemblies Suitable for use on smoke door assemblies Suitable for use on fire and smoke door assemblies
5	Security (personal protection)	1	All emergency exit devices have a critical safety function, therefore only the top grade is identified for the purposes of this European Standard
6	Corrosion resistance		Corrosions resistance
		3 4	High corrosion resistance Very High Corrosion resistance
7	Security (burglary resistance)		test load [N]
		2	1000
8	Projection of operating element		Projection of operating element [mm]
		1 2	≤ 150 ≤ 100

9	Type of operation		Type of operation
		A B W	Handle bar operation Push bar operation Note classification key in the EC- Certificate of Constancy of performance Nr.: 0432-CPR-00007-02 (MPA NRW)
10	Field of door application		Field of door application
		A B C	Outward opening single & double exit door Outward opening single exit door only Outward opening double exit door: inactive leaf only

## 8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Stephan Fischbach, Managing Director

at Albstadt

on 15.01.2016



ASSA ABLOY  
Sicherheitstechnik GmbH  
Bildstockstraße 20  
72458 Albstadt  
DEUTSCHLAND  
Tel. + 497431 123-0  
Fax + 497431 123-240  
www.assaabloy.de

ASSA ABLOY is the  
global leader in door  
opening solutions,  
dedicated to  
satisfying  
end-user needs for  
security, safety and  
convenience.

www.assaabloy.com