



Product description

Model with mechanical unlocking.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Universal voltage
- Compatible with current mortise locks
- Compatible with ProFix® 2 striking plates
- Optimal outlet bevels for gentle interaction with the magnetic latch bolt
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data

Adjustable latch (FF, FaFix®)	Yes
Mechanical unlocking (E)	Yes
Fail-locked	Yes
For magnet latch bolt lock	Yes
Noise damped	Yes
Continuous duty	22-26 V_DC
Rated resistance	200 Ohm
Current consumption 24 V AC	60 mA
Current consumption 24 V DC	120 mA
Max. latch preload AC operation 42 V	350 N
Break-in resistance	3750 N
Height	66 mm
Width	20,1 mm
Max. latch preload AC	200 N
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-15 °C to +40 °C
Max. latch preload DC (stabilised)	50 N
Installation position	Vertical and horizontal
Max. latch preload DC (stabilised) 42 V	200 N
Load cycles for in-plant test	250000
Suitable for fire doors	No

Article number

118ET13-----B71

