

Maxi- Magnet 1200 lbs

Surface-mounted; aluminium; with hall sensor

Product description

Holding magnet suitable for locking doors.

UL-certificated for use with swinging type fire doors rated up to an including $\frac{3}{4}$ h

Surface mounting version with hall effect sensor.

Version with hall effect sensor: magnet contains a contact for locking status monitoring (hall effect sensor). The optical locking indicator is an LED which is visible from outside.

Overview of Advantages

- With lock monitoring

Scope of delivery

- Holding magnet with counter plate

Note

- A contact is integrated in the magnet for lock monitoring (hall sensor).

Accessories/Individual parts

- Mounting bracket L-shaped; for maxi magnets aluminium version MAGAC-L500-----
- Mounting plate MAGAC-Z500Z-shaped; for maxi-magnets, in aluminium MAGAC-Z500-----
- Mounting plate MAGAC-M500 For fixing holder striking plates from the 5000 N series MAGAC-M500-----
- Universal mounting bracket MAGAC-U300Z-shaped; variable; for 3000/ 5000 N magnets in aluminium MAGAC-U300/500-

Technical data

Input operating voltage	12 or 24 V DC
Current consumption 12 V DC	677 mA
Current consumption 24 V DC	438 mA
Holding power	1200 lbs
Surface	Aluminium
Length	266 mm
Width	68 mm
Depth	40 mm
Hall sensor	Yes
UL-certification	UL 10B / UL 10C / fire rating $\frac{3}{4}$ h

Article number	MAG-5-UL-ALS-HD
EAN-Number	4042203676169

