



### Product description

Model with adjustable FaFix® latch and mechanical unlocking (for daytime unlocking).

### Overview of Advantages

- Suitable for all common striking plates
- Can be combined with striking plates with latch bolt guide (standard) without FaFix®
- Due to 180° fitting, can be used DIN right and left

### Scope of delivery

- 1 piece electric strike

### Note

- Order code for version DIN right = 14AEFF

### Technical data

Handing potential	Universal
Adjustable latch (FF, FaFix®)	Yes
Mechanical unlocking (E)	Yes
Fail-locked	Yes
Rated resistance	16.5 Ohm
Current consumption AC 12 V	500 mA
Current consumption AC 16 V	700 mA
Current consumption AC 8 V	350 mA
Current consumption DC (50% Residual ripple) 12 V	710 mA
Current consumption DC (50% Residual ripple) 16 V	940 mA
Current consumption DC (50% Residual ripple) 8 V	470 mA
Current consumption DC (stabilized) 12 V	725 mA
Current consumption DC (stabilized) 16 V	970 mA
Current consumption DC (stabilized) 8 V	485 mA
Break-in resistance	4000 N
Height	90 mm
Width	20 mm
Depth	28 mm
Operating temperature range	-15 °C to +40 °C
Installation position	Vertical and horizontal
Material housing	Zinc die-cast
Latch material	Zinc die-cast

Article number 14EFF-----R11

EAN-Number 4042203035331

