

Product description

Model with monitoring contact as potential-free changeover contact. This is actuated via a latch bolt slider. Door strike can be adjusted in the striking plate, thus making installation work a great deal easier.

Overview of Advantages

- Suitable for all common striking plates
- Can be combined with striking plates with latch guide (model St.)
- Reversible design = DIN right (DR=5)

Scope of delivery

- 1 piece electric strike

Note

- Order code for version DIN right = 14ARRF

Technical data

Handing	Universal
potential	8-16 V AC/DC
Adjustable electric strike (F, Fix®)	Yes
Monitoring contact (RR)	Yes
Fail-locked	Yes
Rated resistance	16.5 Ohm
Current consumption AC 12 V	500 mA
Current consumption AC 16 V	700 mA
Current consumption AC 8 V	350 mA
Current consumption DC (50% Residual ripple) 12 V	710 mA
Current consumption DC (50% Residual ripple) 16 V	940 mA
Current consumption DC (50% Residual ripple) 8 V	470 mA
Current consumption DC (stabilized) 12 V	725 mA
Current consumption DC (stabilized) 16 V	970 mA
Current consumption DC (stabilized) 8 V	485 mA
Break-in resistance	5000 N
Height	112 mm
Width	20 mm
Depth	28 mm
Operating temperature range	-15 °C to +40 °C
Installation position	Vertical and horizontal
Material housing	Zinc die-cast
Latch material	Steel
Max. latch preload AC operation 8 V	110 N
Max. latch preload AC operation 12 V	80 N
Max. latch preload AC operation 16 V	100 N
Max. keep pre-load DC (50% Residual ripple) 8 V	10 N
Max. latch preload DC (50% ripple) 12 V	20 N
Max. latch preload DC (50% ripple) 16 V	40 N
Max. latch preload DC (stabilised) 8 V	10 N
Max. latch preload DC (stabilised) 12 V	10 N
Max. latch preload DC (stabilised) 16 V	20 N

Article number	14RRF-----R11
EAN-Number	4042203041851

