

Product description

Model with monitoring contact as potential-free changeover contact. This is actuated via a latch bolt slider. Door strike can be adjusted in the striking plate, thus making installation work a great deal easier.

Overview of Advantages

- Suitable for all common striking plates
- Can be combined with striking plates with latch guide (model St.)
- Reversible design = DIN right (DR=5)

Scope of delivery

- 1 piece electric strike

Note

- Order code for version DIN right = 14ARRF

Technical data

Handing	Universal
potential	12 V DC eE
Adjustable electric strike (F, Fix®)	Yes
Monitoring contact (RR)	Yes
Fail-locked	Yes
Rated operating voltage tolerance range	±1 V
Rated resistance	60 Ohm
current consumption	125 mA
Current consumption DC (50% Residual ripple)	190 mA
Current consumption DC (stabilised)	200 mA
Break-in resistance	5000 N
Height	112 mm
Width	20 mm
Depth	28 mm
Operating temperature range	-15 °C to +40 °C
Max. latch preload AC	100 N
Installation position	Vertical and horizontal
Max. keeper pre-load DC (50% residual ripple)	50 N
Max. latch preload DC (stabilised)	40 N
Material housing	Zinc die-cast
Latch material	Steel

Article number 14RRF- - - - - E31

EAN-Number 4042203041820

