

Product description

Model with recovery diode for access control systems. Door strike can be adjusted in the striking plate, thus making installation work easier.

Overview of Advantages

- The universal strike in a solid design
- Suitable for all common striking plates
- Can be combined with striking plates with latch bolt guide (standard) without FaFix®
- Due to 180° fitting, can be used DIN right and left

Scope of delivery

- 1 piece electric strike

Note

- Order code for version DIN right = 1405AF

Technical data

Handing	Universal
potential	24 V DC eE
Adjustable electric strike (F, Fix®)	Yes
Diode (05)	Yes
Fail-locked	Yes
Rated operating voltage tolerance range	±2 V
Rated resistance	235 Ohm
current consumption	70 mA
Current consumption DC (50% Residual ripple)	100 mA
Current consumption DC (stabilised)	102 mA
Break-in resistance	6500 N
Height	90 mm
Width	20 mm
Depth	28 mm
Operating temperature range	-15 °C to +40 °C
Max. latch preload AC	80 N
Installation position	Vertical and horizontal
Max. keeper pre-load DC (50% residual ripple)	35 N
Max. latch preload DC (stabilised)	25 N
Material housing	Zinc die-cast
Latch material	Steel

Article number	1405F-----F31
EAN-Number	4042203046054

