



Product description

Model with adjustable FaFix® latch which features electric strike latch alignment.

Overview of Advantages

- Can be combined with striking plates with latch bolt guide (standard) without FaFix®
- Due to 180° fitting, can be used DIN right and left

Scope of delivery

- 1 piece electric strike

Note

- Order code for version DIN right = 24AFF

Technical data

Handing	Universal
potential	6-12 V AC/DC
Adjustable latch (FF, FaFix®)	Yes
Fail-locked	Yes
Hold-open function	Yes
Rated resistance	7.7 Ohm
Current consumption AC 12 V	1100 mA
Current consumption AC 6 V	550 mA
Current consumption DC (50% Residual ripple) 12 V	1480 mA
Current consumption DC (50% Residual ripple) 6 V	740 mA
Current consumption DC (stabilized) 12 V	1560 mA
Current consumption DC (stabilized) 6 V	780 mA
Break-in resistance	4000 N
Height	90 mm
Width	20 mm
Depth	28 mm
Operating temperature range	-15 °C to +40 °C
Material housing	Zinc die-cast
Latch material	Zinc die-cast
Max. latch preload AC operation 6 V	160 N
Material surface-mounted attachment	Zinc die-cast
Max. latch preload AC operation 12 V	160 N
Max. latch preload DC (50% ripple) 6 V	40 N
Max. latch preload DC (50% ripple) 12 V	100 N
Max. latch preload DC (stabilised) 6 V	10 N
Max. latch preload DC (stabilised) 12 V	60 N

Article number

24FF- - - - - D11

EAN-Number

4042203259645

