



Product description

Model with adjustable FaFix® latch and mechanical unlocking (for daytime unlocking).

Overview of Advantages

- Suitable for all common striking plates
- Can be combined with striking plates with latch bolt guide (standard) without FaFix®
- Due to 180° fitting, can be used DIN right and left

Scope of delivery

- 1 piece electric strike

Note

- Order code for version DIN right = 24AEFF

Technical data

| | |
|---|------------------|
| Handing potential | Universal |
| Adjustable keeper (FF, FaFix®) | Yes |
| Mechanical unlocking (E) | Yes |
| Fail-locked | Yes |
| Hold-open function | Yes |
| Rated resistance | 7.7 Ohm |
| Current consumption AC 12 V | 1100 mA |
| Current consumption AC 6 V | 550 mA |
| Current consumption DC (50% Residual ripple) 12 V | 1480 mA |
| Current consumption DC (50% Residual ripple) 6 V | 740 mA |
| Current consumption DC (stabilized) 12 V | 1560 mA |
| Current consumption DC (stabilized) 6 V | 780 mA |
| Break-in resistance | 4000 N |
| Height | 90 mm |
| Width | 20 mm |
| Depth | 28 mm |
| Operating temperature range | -15 °C to +40 °C |
| Material housing | Zinc die-cast |
| Latch material | Zinc die-cast |
| Material surface-mounted attachment | Zinc die-cast |

Article number

24EFF-----D11

