



Product description

Model with monitoring contact, actuated by the latch bolt.

Overview of Advantages

- Water-proof for use outdoors
- Protection rating IP54 for the electrical components
- Connecting cable 300 mm length
- Equipped with bipolar protective diodes
- Radius keeper, FaFix®, adjustable by 3 mm
- Compatible with current mortise locks
- Striking plates with 2 position settings available
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Note

- Not an authorised locking system for doors along escape and rescue routes

Technical data

Handing	Universal
potential	24 V DC
Noise damped	Yes
Adjustable latch (FF, FaFix®)	Yes
Monitoring contact (RR)	Yes
Fail-unlocked	Yes
Bi-directional diode	Yes
Rated resistance	160 Ohm
Monitoring contact switching current	250 mA AC/DC
Current consumption 24 V DC	150 mA
Monitoring contact switching voltage	12-24 V AC/DC
Break-in resistance	3750 N
Height	67 mm
Max. latch preload DC (stabilised)	30 N
Width	18 mm
Depth	26 mm
FaFix® adjustment range	3 mm
Latch bolt engaging depth	5,5 mm
Operating temperature range	-40 °C to +50 °C
Installation position	Vertical and horizontal
Load cycles for in-plant test	250000

Article number	138WR- - - - - F91
----------------	--------------------

