



Product description

Electric strikes for fire doors with an exceptionally sturdy design.

Model with adjustable FaFix® latch and monitoring contact

Can also be used as a security electric strike.

Overview of Advantages

- Sturdy precision-casted steel casing
- Reliable unlocking under preload
- Horizontal fitting permitted

Scope of delivery

- 1 piece electric strike

Note

- Please refer to the information provided from the Deutsches Institut für Bautechnik (German Institute for Structural Engineering).
- Picture and text show DIN left hand, DIN right hand is mirror-inverted

Technical data

Handing	Right-hand
potential	24 V AC/DC
Adjustable keeper (FF, FaFix®)	Yes
Monitoring contact (RR)	Yes
Fail-locked	Yes
Rated operating voltage tolerance range	± 2 V
Rated resistance	43 Ohm
current consumption	550 mA
Current consumption DC (stabilised)	560 mA
Break-in resistance	10000 N
Height	134 mm
Width	23 mm
Depth	39 mm
Operating temperature range	-15 °C to +40 °C
Installation position	Vertical and horizontal
Material housing	Steel
Latch material	Steel
Material surface-mounted attachment	Steel
Certified in compliance with	DIN EN 14846:2008
Max. latch preload AC	600 N
Max. latch preload DC (stabilised)	600 N
DIN-direction	Right-hand

Article number	131RRFF- - - - F15
EAN-Number	4042203152120

