



### Product description

Model with basic equipment. Also useable as a heavy-duty electric strike.

### Overview of Advantages

- Radius keeper, FaFix®, adjustable by 4 mm
- 12-24 Volt voltage range for AC and DC operation
- New connection technology, can be replugged
- Resistant to continuous current across the entire voltage range
- All models can be fitted as required (right-hand/left-hand/horizontally)
- Integrated suppressor diode
- Compatible with Model Range 142U
- Preload modes 400N or 800N can be set

### Scope of delivery

- 1 piece electric strike
- 1 operating manual

### Technical data

Handing	Right-hand
potential	12 - 24 V AC/DC eE
Adjustable keeper (FF, FaFix®)	Yes
Fail-locked	Yes
TVS diode	Yes
Fail-locked	Yes
Input operating voltage	12/24 V
Max. start current consumption at 12 V DC	500 mA
Max. start current consumption at 24 V DC	250 mA
Current consumption 12 V AC/DC	165 mA
Current consumption 24 V AC/DC	80 mA
Max. pre-load	400 N / 800 N
Manufacturer's certificate No.	P-120003624
Break-in resistance	8000 N
Height	79 mm
Width	20 mm
Depth	28 mm
FaFix® adjustment range	4 mm
Latch bolt engaging depth	6 mm
Operating temperature range	-15 °C to +40 °C
Continuous function load cycles	200000
Load cycles for in-plant test	500000
Installation position	Vertical and horizontal
Certified in compliance with	DIN EN 14846:2008
DIN-direction	Right-hand
Suitable for fire doors	Yes

Article number 143- - - - - Q35

EAN-Number 4042203460713

