



### Product description

Main use is as a supplementary electronic locking device in sanitary facilities (WC) with 2 entrances in hospitals and nursing homes. Combined with a bolt switch contact model 878 or 875, when one door is mechanically locked, the lock in the opposite door

Interlocking functions can be easily controlled using models with monitoring contacts.

The particular advantage of this type series is its almost silent operation. Due to its special design, there is no clicking sound like the one usually heard in electric strikes when the door is opened.

### Overview of Advantages

- DIN left and right usable
- Almost silent operation

### Scope of delivery

- 1 piece electric strike
- 1 mating component
- 1 operating manual

### Note

- As this electric strike is combined with a mating part, the door cannot be opened if the power or the electronics fail. Preferably use emergency power supply systems as a power source.

### Technical data

|   |                         |
|---|-------------------------|
| Handing   | Universal               |
| potential   | 6-12 V AC/DC            |
| Fail-locked                                       | Yes                     |
| Rated resistance                                  | 7.7 Ohm                 |
| Current consumption AC 12 V                       | 1100 mA                 |
| Current consumption AC 6 V                        | 550 mA                  |
| Current consumption DC (50% Residual ripple) 12 V | 1480 mA                 |
| Current consumption DC (50% Residual ripple) 6 V  | 740 mA                  |
| Current consumption DC (stabilized) 12 V          | 1560 mA                 |
| Current consumption DC (stabilized) 6 V           | 780 mA                  |
| Break-in resistance                               | 3000 N                  |
| Height  | 90 mm                   |
| Width   | 20 mm                   |
| Depth   | 16 mm                   |
| Operating temperature range                       | -15 °C to +40 °C        |
| Installation position                             | Vertical and horizontal |
| Material housing                                  | Zinc die-cast           |
| Latch material                                    | Zinc die-cast           |
| DIN-direction                                     | universal               |

|                |                   |
|----------------|-------------------|
| Article number | 9314- - - - - D11 |
|----------------|-------------------|

