

Product description

Main use is as a supplementary electronic locking device in sanitary facilities (WC) with 2 entrances in hospitals and nursing homes. Combined with a bolt switch contact model 878 or 875, when one door is mechanically locked, the lock in the opposite door

Interlocking functions can be easily controlled using models with monitoring contacts.

The particular advantage of this type series is its almost silent operation. Due to its special design, there is no clicking sound like the one usually heard in electric strikes when the door is opened.

Overview of Advantages

- With 12/24 V changeover switch including TVS diode (e.g. to combine with access control systems)
- Integrated monitoring contact
- DIN left and right usable
- Almost silent operation

Scope of delivery

- 1 piece electric strike

Technical data

Handing	Universal
potential	12 - 24 V AC/DC eE
Monitoring contact (RR)	Yes
Diode (05)	Yes
Fail-locked	Yes
Nominal resistance 12 V	58
Nominal resistance 24 V	230
Current consumption AC 12 V	130 mA
Current consumption AC 24 V	70 mA
Current consumption DC (50% Residual ripple) 12 V	190 mA
Current consumption DC (50% ripple) 24 V	105 mA
Current consumption DC (stabilized) 12 V	210 mA
Current consumption DC (stabilised) 24 V	105 mA
Break-in resistance	3000 N
Operating temperature range	-15 °C to +40 °C
Installation position	Vertical and horizontal
Material housing	Zinc die-cast
Latch material	Zinc die-cast
DIN-direction	universal

Article number	9314UR- - - - - Q31
EAN-Number	4042203415096

