

High- security handle control 709X702PZX

12-24 V DC; backset 65

Product description

The security lock with handle control 709X is used especially in situations where the advantages of handle-controlled unlocking have to be combined with the mechanical security requirements of the above-mentioned lock models 309X and 409X. The integrated

The bolt is pulled back by the coupled door handle and the blocking of the double action latch is lifted. When closing the doors the control latch, together with the double action latch, actuates the solid bolting of the preloaded bolt and the blocking of the double action latch, which therefore serves as an additional lock.

The DIN direction DIN L/DIN R settings and selecting between fail-locked and fail-unlocked can be performed on the lock as required.

Overview of Advantages

- Mechanical automatic locking system
- Mechanical follow up control between double action latch and control latch
- With double action lock, so can be used with both DIN left-hand and right-hand
- Suitable for fire doors
- Handle follower controllable outside and inside
- Changeover function for unlocking with a key from the outside
- Monitoring functions

Note

- 729X...PZX series locks feature a continuous handle follower and thus require an inside handle and an outside handle.
- The lock is actuated by a card reader, code lock, timer switch, button, etc.

Technical data

Backset	65 mm
Panic function	No
Operating temperature range	-20 °C to +60 °C
Bolt throw	20 mm
Handle follower	9 mm
Distance	74 mm
Building authorities test certificate	P-120003555
Width face plate	24 mm

Variants that can be ordered

Order number	Description
709X702PZX--G41	709X security lock

