

Mechanical safety lock

309MB2A72A60- - F

Product description

Security Lock 309M with B function is a self-locking panic lock with split follower and mechanically controllable outside handle. The outside handle can be permanently engaged or disengaged via the cylinder.

Overview of Advantages

- Mechanical automatic locking system
- Mechanical automatic locking process control between latch and control latch
- Burglary-resistant thanks to solid, hardened lock bolt with 20 mm throw
- Burglary resistance up to resistance class 2 can be achieved in suitable door systems
- Panic function (approval in accordance with DIN EN 179)
- Suitable for fire doors, evidence of conformity in form of general appraisal certificate
- Outer handle mechanically controlled by activating cylinder, door fitting features split handle spindle and outer handle

Scope of delivery

- 1 x mechanical security lock
- 1 x Operating instructions

Technical data

Handing	Version F
Dead bolt features	Hardened steel surface, 60 HRC
Distance	74 mm
Bolt throw	20 mm
Handle follower	9 mm
Faceplate dimensions	235 x 24 x 3 mm
Approval DIN EN 179	EC Certificate of Conformity 0432 BPR-001
Pressure resistance requirements	Class 5 according to DIN 18251-3
Minimum load capacity of latch bolt	5 kN
Minimum load capacity of bolt	10 kN
Backset	60 mm
Bolt counterpressure	6 kN
Panic function	Yes

Article number

309MB2A72A60--F

