

Mechanical multi-point lock

319EB2V92-55--D

Product description

Multi-Point Lock 319 with B function is a self-locking panic lock with split follower and mechanically controllable outside handle. The outside handle can be permanently engaged or disengaged via the cylinder.

Thanks to its three hardened lock bolts with a 20 mm throw and automatic self-locking, this multi-point lock meets optimum standards in mechanical security.

The enhanced burglary protection achieved as a result does not affect the performance of the lock function. Requirements for its use in fire doors are also met and the lock is also suitable for panic doors in accordance with DIN EN 1125.

Scope of delivery

- 1 x mechanical multi-point lock
- 1 piece striking plate
- 1 operating manual

Technical data

Handing	Version D
DIN EN 1125 approval	EC Certificate of Conformity 0432 BPR-017
Approval DIN EN 179	Certificate of Constancy of performance 0432-CPR-00007-01
Backset	55 mm
Distance	92 mm
Bolt throw	20 mm
Handle follower	9 mm
Faceplate dimensions	1760 x 24 x 6 mm
Panic function	Yes
Pressure resistance requirements	Class 5 according to DIN 18251-3
Minimum load capacity of latch bolt	5 kN
Minimum load capacity of bolt	10 kN
Bolt counterpressure	6 kN
Dead bolt features	Hardened steel surface, 60 HRC

Article number	319EB2V92-55--D
----------------	-----------------

