

MEDIATOR® lock, tubular frame version



Product description

The MEDIATOR® lock in its tubular frame version is available with different backsets and a comprehensive range of accessories.

Overview of Advantages

- Automatic locking system: Bolt and latch are blocked, therefore higher level of security
- Mechanical follow up control between double action latch and control latch
- Integrated panic function via internal door handle
- Changeover function for unlocking with a key from the outside
- Minimum rear backset for tubular frame design: 15 mm

Note

- MEDIATOR® locks have a bolt through the handle and thus require front door furniture (inside handle or panic push bar, outside knob or push bar).

Technical data

Backset	30, 35, 40, 45 mm
Distance	Euro profile cylinder: 92 mm
Type of cylinder	Euro profile cylinder
Bolt throw	20 mm
Handle follower	9 mm
VdS-approval	G 109 032, M 109314, Z 109001
Approval DIN EN 179	Certificate of Constancy of performance 0432-CPR-00007-11
DIN EN 1125 approval	Certificate of Constancy of performance 0432-CPR-00007-12
Building authorities test certificate	P-120003555
Mech. strength (EN 12209:2004)	200,000 cycles, 50N load on latch, Class 6 protection

Variants that can be ordered

Order number	Description
609-102PZ-----1	Tubular frame; backset 30 mm; distance 92 mm; spindle 8-9 mm; angular face plate 24 mm
609-202PZ-----1	Tubular frame; backset 35 mm; distance 92 mm; spindle 8-9 mm; angular face plate 24 mm
609-302PZ-----1	Tubular frame; backset 40 mm; distance 92 mm; spindle 8-9 mm; angular face plate 24 mm
609-402PZ-----1	Tubular frame; backset 45 mm; distance 92 mm; spindle 8-9 mm; angular face plate 24 mm

