



### Product description

Holding magnet in aluminium housing for wall mount, with optional interrupter pushbutton

### Technical data

Supply voltage	24 V DC
Current consumption at 24 V	Model 830-3: 300 N / 20 mA; Model 830-5: 500 N / 25 mA; Model 830-8: 800 N / 45 mA; Model 83012: 1,200 N / 105 mA
Operating temperature range	0 to +50 °C
Certified in compliance with	EN 1155
Height	70 mm
Width	90 mm
Depth	96 mm
Continuous duty	100 % ED
Class of protection	IP 40

### Variants that can be ordered

Order number	Description
830-3IGW----F90	In aluminium housing for wall mount, 300 N holding force, 96 mm wall clearance
830-5IGW----F90	In aluminium housing for wall mount, 500 N holding force, 96 mm wall clearance
830-8IGW----F90	In aluminium housing for wall mount, 800 N holding force, 96 mm wall clearance
83012IGW----F90	In aluminium housing for wall mount, 1,200 N holding force, 96 mm wall clearance
830-3IGWU---F90	In aluminium housing for wall mount with interrupter pushbutton, 300 N holding force, 96 mm wall clearance
830-5IGWU---F90	In aluminium housing for wall mount with interrupter pushbutton, 500 N holding force, 96 mm wall clearance
830-8IGWU---F90	In aluminium housing for wall mount with interrupter pushbutton, 800 N holding force, 96 mm wall clearance
83012IGWU---F90	In aluminium housing for wall mount with interrupter pushbutton, 1,200 N holding force, 96 mm wall clearance