

Door code fittings - minimal installation, maximum effect

Door code armature

Product description

Mechanical operation remains as it was before with the door code escutcheon. Doors can be opened as usual from the inside using the handle. When the correct code number is entered, the door handle on the outside is electrically released.

Use version B for inward-opening, DIN left-hand doors or for outward-opening, DIN right-hand doors.

This model can be used in doors with a door leaf thickness of 38 - 50 mm.

Overview of Advantages

- 2 to 6 digit code modification code can be programmed
- Up to 3 different user codes
- 1,000,000 different code variations possible
- Exterior escutcheon with membrane keypad
- Inner escutcheon with battery case
- Door handle/door handle combination
- Door escutcheon with different rose inserts
- Models available for Swiss round profile cylinders
- Use as organisational tool for daily operations
- For all areas which must only be accessible to authorised persons
- Code-operated lock
- Code management using modification code
- 3 user codes
- Also easily retrofitted to existing doors
- No cabling/wiring required; highly suitable for doors which should not/cannot be wired
- Little installation work required

Scope of delivery

- 1 interior door fitting
- 1 exterior door fitting
- 1 mounting accessory kit
- 1 adapter sleeve
- 1 operating manual

Note


- Rose insert must be ordered separately. A rose insert is not included in the door code fitting supply package.

Accessories/Individual parts

- Rosette inserts for model 49510/49511 For euro profile cylinders; distance 72 mm; white aluminium (RAL 9006) 49510-3-7291-00
- Rosette inserts for model 49510/49511 For euro profile cylinders; distance 72 mm; grey white (RAL 9002) 49510-3-7293-00
- Rosette inserts for model 49510/49511 For euro profile cylinders; distance 72 mm; grey brown (RAL 8019) 49510-3-7295-00
- Rosette inserts for model 49510/49511 For euro profile cylinders; distance 92 mm; white aluminium (RAL 9006) 49510-3-9291-00
- Rosette inserts for model 49510/49511 For euro profile cylinders; distance 92 mm; grey white (RAL 9002) 49510-3-9293-00
- Rosette inserts for model 49510/49511 For euro profile cylinders; distance 92 mm; grey brown (RAL 8019) 49510-3-9295-00
- Rosette inserts for model 49510/49511 Without profile cylinder drill hole; white aluminium (RAL 9006) 49510-7---91-00
- Rosette inserts for model 49510/49511 Without profile cylinder drill hole; grey white (RAL 9002) 49510-7---93-00
- Rosette inserts for model 49510/49511 Without profile cylinder drill hole; grey brown (RAL 8019) 49510-7---95-00

Technical data

Supply voltage	9 V block battery
Door leaf thickness	38 to 50 mm
Version	B
Handle spindle	8, 8.5 and 9 mm (7 mm on request)
Release time	3 seconds
Color	Grey brown RAL 8019
Class of protection	IP 40
Operating temperature range	-10 °C to +50 °C



Door code fittings - minimal installation, maximum effect

Door code armature

Dimensions of external sign	66 x 286 x 30 mm (B x H x T)
Dimensions of inside sign	66 x 286 x 24 mm (B x H x T)
Handle follower	8 mm
<hr/>	
Article number	495108----95B87
EAN-Number	4042203157163