

Electronic keypad door fitting

Electronic keypad door fitting



Overview of Advantages

- Can be used with all European (DIN) mortise locks
- Can be used with standard or narrow profile doors
- For use in indoor areas
- Door leaf between 40 and 100 mm thick, in 10 mm increments
- Can be used with a backset of 25 mm or more
- Outer door handle rotates freely
- Inner door handle always engaged
- Main electronics on outside
- Security-relevant electronics inside
- Battery inside
- Coupling inside
- Mechanical cylinder (optional)
- Existing cylinder can continue to be used
- Handle spindle easily replaced
- Fastened with three bolts
- LED for status display (red/green/orange)

Scope of delivery

- 1 escutcheon with battery (Lithium CR123A) and installation instructions
- Screws and drilling template

Technical data

PINpad	PIN code - 4 up to 6 digits
Surface	ST - Surface stainless steel
Approvals	CE-certified
Dimension	312 x 41 x 10/20 mm (H x W x D)
Version	Basic
Handle	L-Form
Surface	Stainless steel brushed (ST)
Distance	Distance 92 mm / Spindle 9 mm
Door leaf thickness	40-50
Backset	> 25 mm
Battery life	30 openings per day for 49 months
Class of protection	IP 52
Operating temperature range	0°C to 60°C
Relative humidity	< 85 % (condensation-free)
Door status	LED (red/green/orange)
Article number	500110-9A11111-