



### Product description

Model with monitoring contact as potential-free changeover contact. This is actuated by the latch bolt via a slide.

### Overview of Advantages

- Suitable for all common striking plates
- Can be combined with striking plates with latch guide (model St.)
- Reversible design = DIN right (DR=5)

### Note

- Order code for version DIN right = 14ARR

### Technical data

|                             |                         |
|-----------------------------|-------------------------|
| Monitoring contact (RR)     | Yes                     |
| Fail-locked                 | Yes                     |
| Break-in resistance         | 5000 N                  |
| Height                      | 120 mm                  |
| Width                       | 20 mm                   |
| Depth                       | 28 mm                   |
| Operating temperature range | -15 °C to +40 °C        |
| Installation position       | Vertical and horizontal |
| Material housing            | Zinc die-cast           |
| Latch material              | Steel                   |

### Variants that can be ordered

| Order number | Description  |
|--------------|--|
| 14RR-----D11 | Without face plate, 6-12 V AC/DC                   |
| 14RR-----R11 | Without face plate, 8-16 V AC/DC                   |
| 14RR-----F11 | Without face plate, 24 V AC/DC                     |
| 14RR-----E31 | Without striking plate, 12 V DC electric unlocking |
| 14RR-----F31 | Without striking plate, 24 V DC electric unlocking |

