

Product description

Model with reversible design. The advantage of this design is that the connection also points upwards in the DIN right-hand version. This means the cable conduit is not placed near the deadbolt. Adjustable FaFix® latch which features electric strike latch alignment.

Overview of Advantages

- The minimum gap between the strike latch and casing lower surface enables DL and DR designs to be combined with locks which contain a minimum latch deadbolt clearance.
- For striking plates with minimum latch deadbolt clearance
- Can be combined with striking plates with latch bolt guide (standard) without FaFix®

Scope of delivery

- 1 piece electric strike

Technical data

Handing	Right-hand
potential	24 V DC eE
Adjustable latch (FF, FaFix®)	Yes
Fail-locked	Yes
Rated operating voltage tolerance range	± 2 V
Rated resistance	235 Ohm
current consumption	70 mA
Current consumption DC (50% Residual ripple)	100 mA
Current consumption DC (stabilised)	102 mA
Break-in resistance	4000 N
Height	104 mm
Width	20 mm
Depth	28 mm
Operating temperature range	-15 °C to +40 °C
Max. latch preload AC	80 N
Installation position	Vertical
Max. keeper pre-load DC (50% residual ripple)	35 N
Max. latch preload DC (stabilised)	25 N
Material housing	Zinc die-cast
Latch material	Zinc die-cast
Material surface-mounted attachment	Zinc die-cast

Article number	14SFF-----F35
EAN-Number	4042203043763

