



Product description

Model with recovery diode for access control systems, with reversible design. The advantage lies in the fact that the connection also points upwards in the DIN right-hand version. This means the cable conduit is not near the deadbolt. Adjustable FaFix latch which enables door strike latch to be aligned.

Overview of Advantages

- The universal strike in a solid design
- The minimum gap between the strike latch and casing lower surface enables DL and DR designs to be combined with locks which contain a minimum latch deadbolt clearance.
- For striking plates with minimum latch deadbolt clearance
- Suitable for all common striking plates
- Can be combined with striking plates with latch bolt guide (standard) without FaFix®

Technical data

Adjustable latch (FF, FaFix®)	Yes
Diode (05)	Yes
Fail-unlocked	Yes
Break-in resistance	4000 N
Height	104 mm
Width	20 mm
Depth	28 mm
Operating temperature range	-15 °C to +40 °C
Material housing	Zinc die-cast
Latch material	Zinc die-cast
Material surface-mounted attachment	Zinc die-cast

Variants that can be ordered

Order number	Description
3405SFF-----E94	Without striking plate, 12 V DC
3405SFF-----E95	Without striking plate, 12 V DC
3405SFF-----F94	Without striking plate, 24 V DC
3405SFF-----F95	Without striking plate, 24 V DC

