

Product description

Model with connection cable, 2 x 0.5 x 2,500 mm.

Overview of Advantages

- Radius keeper, FaFix®, adjustable by 3 mm
- Universal voltage
- Compatible with current mortise locks
- Compatible with available striking plates
- Symmetrical design. DIN left/right as well as horizontal applicable

Scope of delivery

- 1 piece electric strike

Technical data

| | |
|---|-------------------------|
| Handing | Universal |
| potential | 10-24 V AC/DC |
| Noise damped | Yes |
| Adjustable keeper (FF, FaFix®) | Yes |
| Fail-locked | Yes |
| Hold-open function | Yes |
| Continuous duty | 11-13 V_DC |
| Rated resistance | 43 Ohm |
| Current consumption 12 V AC | 250 mA |
| Current consumption 12 V DC | 280 mA |
| Current consumption 24 V AC | 500 mA |
| Current consumption 24 V DC | 560 mA |
| Break-in resistance | 3750 N |
| Height | 66 mm |
| Width | 16 mm |
| Depth | 26 mm |
| FaFix® adjustment range | 3 mm |
| Latch bolt engaging depth | 5,5 mm |
| Operating temperature range | -15 °C to +40 °C |
| Max. latch preload AC operation 12 V | 200 N |
| Installation position | Vertical and horizontal |
| Load cycles for in-plant test | 250000 |
| Max. latch preload DC (stabilised) 12 V | 50 N |
| Suitable for fire doors | No |
| Max. latch preload DC (stabilised) 24 V | 200 N |

| | |
|----------------|-------------------|
| Article number | 128K- - - - - A71 |
| EAN-Number | 4042203430310 |

