

### Overview of Advantages

- Can be used with all European (DIN) mortise locks
- Can be used with standard or narrow profile doors
- For indoor use
- Door leaf between 40 and 100 mm thick, in 10 mm increments
- Can be used with a backset of 25 mm or more
- Outer door handle rotates freely
- Inner door handle always engaged
- Main electronics on outside
- Security-relevant electronics inside
- Battery inside
- Coupling inside
- Mechanical cylinder (optional)
- Existing cylinder can continue to be used
- Handle spindle easily replaced
- Fastened with three bolts
- LED for status display (red/green/orange)

### Scope of delivery

- 1 escutcheon with battery (Lithium CR123A) and installation instructions
- Screws and drilling template

### Technical data

LED display	LED (red/green/orange)
Battery life	30 openings per day for 49 months
Surface	Stainless steel brushed (ST)
Dimension	312 x 41 x 10/20 mm (H x W x D)
Operating temperature range	0°C to 60°C
Door leaf thickness	Door thickness 60-70 mm
Backset	> 25 mm
Version	Basic - Interior doors up to grade 2
Handle	L-Form
PINpad	PIN code - 4 up to 6 digits
Required power supply	1 x Lithium CR123A
Class of protection	IP 52
Article / Feature	Without cylinder; door thickness 60 - 70 mm; Spindle 10 mm
Approvals	CE-certified
<b>Article number</b>	<b>500110-0C--111-</b>