



Product description

Can be used for all European (DIN) mortise locks. For wooden, steel or tubular frame doors. The main electronics are outside, the security-relevant electronics are inside. Outer door handle rotates freely, inner door handle always engaged. Memory capacity for up to 99 PIN codes. LED for status display.

Overview of Advantages

- Can be used with all European (DIN) mortise locks
- Can be used with standard or narrow profile doors
- For indoor use
- Easy installation
- Right-hand or left-hand stop can be freely selected during mounting
- In the event of changes, ESA501 can also be modified retrospectively via an optional set
- Adjustment of the door leaf thickness from 40 to 100 mm in 10 mm increments
- Can be used with a backset of 40 mm or more
- Outer door handle rotates freely
- Inner door handle always engaged
- Main electronics on outside
- Security-relevant electronics inside
- Battery and coupling inside
- Mechanical cylinder (optional)
- Existing cylinder can continue to be used
- Handle spindle easily replaced
- Fastened with three bolts
- LED for status display (red/green/orange)

Scope of delivery

- 1 escutcheon with battery (Lithium CR123A) and installation instructions
- Screws and drilling template

Technical data

Surface	ST
Surface	ST - Surface stainless steel
Version	Premium
PINpad	PINpad
Handle	U-Shape

Variants that can be ordered

Order number	Description
50111A-9K--211-	Without PZ; door thickness 40 - 45 mm; Spindle 9 mm
50111A-9L--211-	Without PZ; door thickness 45 - 50 mm; Spindle 9 mm
50111A-9M--211-	Without PZ; door thickness 50 - 55 mm; Spindle 9 mm
50111A-9N--211-	Without PZ; door thickness 55 - 60 mm; Spindle 9 mm
50111A-9O--211-	Without PZ; door thickness 60 - 65 mm; Spindle 9 mm
50111A-9P--211-	Without PZ; door thickness 65 - 70 mm; Spindle 9 mm
50111A-9Q--211-	Without PZ; door thickness 70 - 75 mm; Spindle 9 mm
50111A-9R--211-	Without PZ; door thickness 75 - 80 mm; Spindle 9 mm
50111A-9S--211-	Without PZ; door thickness 80 - 85 mm; Spindle 9 mm
50111A-9T--211-	Without PZ; door thickness 85 - 90 mm; Spindle 9 mm
50111A-9U--211-	Without PZ; door thickness 90 - 95 mm; Spindle 9 mm
50111A-9V--211-	Without PZ; door thickness 95 - 100 mm; Spindle 9 mm