



### Security door code fitting

### Product description

Can be used for all European (DIN) mortise locks. For wooden, steel or tubular frame doors. The main electronics are outside, the security-relevant electronics are inside. Outer door handle rotates freely, inner door handle always engaged. Memory capacity for up to 99 PIN codes. LED for status display.

### Overview of Advantages

- Can be used with all European (DIN) mortise locks
- Can be used with standard or narrow profile doors
- For indoor use
- Door leaf between 40 and 100 mm thick, in 5 mm increments
- Can be used with a backset of 25 mm or more
- Outer door handle rotates freely
- Inner door handle always engaged
- Main electronics on outside
- Security-relevant electronics inside
- Battery inside
- Coupling inside
- Mechanical cylinder (optional)
- Existing cylinder can continue to be used
- Handle spindle easily replaced
- Fastened with three bolts
- LED for status display (red/green/orange)

### Scope of delivery

- 1 escutcheon with battery (Lithium CR123A) and installation instructions
- Screws and drilling template

### Technical data

PINpad	PIN code - 4 up to 6 digits
Surface	ST - Surface stainless steel
Approvals	CE, EN179, EN1906, DIN18273
Version	Premium
Dimension	312 x 41 x 10/20 mm (H x W x D)
Handle	U-Shape
Surface	Stainless steel brushed (ST)
Door leaf thickness	Door thickness 60-65 mm
Backset	> 25 mm
Battery life	30 openings per day for 49 months
Class of protection	IP54
Operating temperature range	-25°C to 60°C
Relative humidity	< 85 % (condensation-free)
Door status	LED (red/green/orange)

Article number	50111A-90--211-
----------------	-----------------