

Universal locking lever cylinder - system SK5 0449,AUS=E29

30 mm diameter, laterally flattened to 22 mm

Overview of Advantages

- The locking direction of the locking lever can be given when ordering; the locking direction can however be easily changed by changing the position of the stop screw

Product description

- 5 pin tumblers
- Brass cylinder
- Standard finish, matt chrome-plated (OF=MC)
- Other surfaces: satin nickel-plated (OF=MV), brass, mat brushed (OF=MG), polished brass (OF=MP)
- Drilling protection (AB=), locking wave (SW=), additional lateral scanning, security card depending on profile (PR=)
- Spherical cylinder core head with reinforced key guide
- Core pins made of special wear-resistant bronze
- Locking lever path 90°
- Fixing with M30x1.5 housing nut
- Two locking lever end positions
- Key rotation 360° (2 key retraction positions)
- Locking lever SLHB= 1647004 (other locking levers available on request)
- Key with round metal head
- Available for individual lockings and locking systems

Scope of delivery

- 1 locking lever cylinder
- 2 nickel silver keys
- 1 housing nut M30 x 1.5 x 4
- 2 core nuts M10 x 0,75 x 3
- locking lever fixed

Ordering Information

- Not available with drilling protection 2 (AB=2) or 3 (AB=3)
- Please include the desired locking path (SST=) in your order.

Suitable ASSA ABLOY products

- Maintenance spray 8511
- Escutcheon with rain protection cover 1254,AUS=1

