

Locking lever cylinder - system P6 P643

25 mm diameter, laterally flattened to 22 mm

Overview of Advantages

- The locking direction of the locking lever can be given when ordering; the locking direction can however be easily changed by changing the position of the stop screw

Product description

- 6 pin tumblers
- Brass cylinder
- Standard finish, matt chrome-plated (OF=MC)
- Other surfaces: satin nickel-plated (OF=MV), brass, mat brushed (OF=MG), polished brass (OF=MP)
- Drilling protection (AB=), security card depending on profile (PR=)
- Tapered cylinder core head with reinforced key guide
- Core pins made of special wear-resistant bronze
- Locking path and locking lever path 90° left or right
- Fixing with M25 x 0.75 housing nut
- Suitable for material thicknesses up to 16 mm
- Standard locking lever (SLHB=1645009)
- Key with square metal head
- Available for locking systems in different system types (AA=...)

Scope of delivery

- 1 locking lever cylinder
- 2 nickel silver keys
- 1 housing nut M25 x 0.75 x 4
- 1 core nut M10 x 0,75

Ordering Information

- Not available with drilling protection 1 (AB=1) or 0+1 (AB=0+1)
- Please include the desired locking path (SST=) in your order.

Suitable ASSA ABLOY products

- Maintenance spray 8511
- Escutcheon with rain protection cover 1254,AUS=2-7

