



Cylinder padlock 0316,AUS=LH25

With positive locking - key can only be extracted when locked



New

Product description

- 5 pin tumblers
- Housing chrome-plated in brass
- Cylinder, nickel-plated brass satin
- Standard shackle clearance height 25 mm (AUS=LH25)
- Optionally with non-corroding shackles (AUS=LH25-NIRO)
- Other shackle heights (AUS=LH50, LH75, LH28/5)
- Steel shackle, diameter 8 mm, hardened and chrome-plated
- Steel shackle diameter 5 mm at shackle height 28 mm (AUS=LH28/5), hardened and chrome-plated
- Locking wave (SW=), additional lateral scanning and security card depending on profile (PR=)
- Spherical / Tapered cylinder core head with reinforced key guide
- Core pins made of special wear-resistant bronze
- Standard version as per DIN EN 12320 class 3 (not valid for AUS=LH28/5)
- Optionally available without controlled locking (AUS2= OHNE ZWANGSSCHL)
- Optionally IP67 certified with protective cap (SUR=2)
- Key with round metal head
- Available for individual lockings and locking systems

Scope of delivery

- 1 cylinder padlock
- 2 nickel silver keys

Suitable ASSA ABLOY products

- Maintenance spray 8511
- Protective cap IP67 1090