

Drive unit for multipoint locking device with lateral bolt 9261

Type .261 - without external cylinder .063

Overview of Advantages

- With robust bolt and solid lock case

Product description

- Visual locking display (green/red)
- Available in color: silver grey (FB=SGR) similar to RAL 9006, white (FB=WS) similar to RAL 9016 and brown (FB=BN) similar to RAL 8019
- With drilling protection for lock cases
- Die-cast anti-corrosive zinc lock case
- Rods and rod covers for door height up to 2400 mm (1 x approx. 1000 mm + 1 x approx. 1400 mm)
- Brass lateral bolt, solid, double turn, 24 mm projection
- Bolt projection via rods, single turn, 17 mm
- Adjustable backset 60/70 mm
- Suitable for DIN left (S=R) or DIN right (S=L)
- For rebated and non-rebated doors

Scope of delivery

- 1 drive unit
- 1 drilling protection for lock case 1920
- Lock case shims (2x 1 mm und 2x 3 mm) for height adjustment up to 18 mm
- 1 set connection components 1954,AUS=TH240

Note

- VdS approval only in combination with a security escutcheon 1086 or 1087

Ordering Information

- Please include the desired color (FB=) as well as the DIN-door direction (S=) in your order.

Suitable ASSA ABLOY products

- External cylinder .063

Accessories/Individual parts

- Bolt for multipoint locking systems 1080
- Bolt set 1081
- Bolt set 1083
- Shim for lock case 1948,ABM=1
- Shim for lock case 1948,ABM=3
- Drilling protection for lock cases 1920
- Shim for lockcase 1949
- Cylinder cover 1086
- Cylinder cover 1087
- Striking plate for lock case 1938,VAR=1475168
- Striking plate 1938,VAR=1475173
- Striking plate for lock case with angle 1938,VAR=1485433

Variants that can be ordered

Article number	FB=	S=
9261 50407	SGR	L
9261 40443	SGR	R
9261 40523	WS	L
9261 40526	WS	R
9261 50408	BN	L
9261 40444	BN	R

