

Steel security fitting with cylinder cover - handle/handle S4K3,VAR=FS

Short backplate for fire doors

Product description

- Distance 72 mm
- Spindle 9 mm
- For cylinder projection from 9 to 13.5 mm
- External plate thickness 10 mm - Internal plate thickness 6 mm
- Material external plate: solid steel, hardened
- Material internal plate: solid steel
- Double screwed
- Handle anodised aluminium with steel core
- Suitable for fire doors

Scope of delivery

- 1 Set with fixing material

Note

- The fitting variant VAR=FS is a fire security fitting approved by MPA Dortmund.

Ordering Information

- Please order VAR=A for use with IKON profile locking cylinders with ARCUS, AEP10 and ASP profiles

Suitable ASSA ABLOY products

- Profile-double cylinder .531
- Profile-double cylinder .551
- Profile-knob cylinder .534,KNF=1
- Profile-knob cylinder .534,KNF=2
- Profile-knob cylinder .534,KNF=7
- Profile-knob cylinder .534,KNF=9
- Profile-knob cylinder .534,KNF=91
- Profile-knob cylinder .534,KNF=92
- Profile-knob cylinder .534,KNF=94

Accessories/Individual parts

- Steel shim for short plate S421

Variants that can be ordered

Article number	FB=	TS=
S4K3,VAR=FS	F1	40 (38-43)
	F1	45 (41-45)
	F1	50 (41-50)
	F1	55 (48-54)
	F1	60 (53-60)
	F1	65 (58-64)
	F1	70 (63-70)
	F1	75 (68-74)
	F1	80 (73-80)
	F1	85 (78-84)
	F1	90 (83-94)
	F1	95 (88-94)
	F1	100 (93-104)
	F1	110 (103-114)
	F2	40 (38-43)
	F2	45 (41-45)
	F2	50 (41-50)
	F2	55 (48-54)
	F2	60 (53-60)
	F2	65 (58-64)
	F2	70 (63-70)
	F2	75 (68-74)
	F2	80 (73-80)
	F2	85 (78-84)
	F2	90 (83-94)
	F2	95 (88-94)
	F2	100 (93-104)
	F2	110 (103-114)

