

Universal locking lever cylinder with adjustable lever distance

.449,AUS=E29- 34

30 mm diameter, laterally flattened to 22 mm

Overview of Advantages

- The locking direction of the locking lever can be given when ordering; the locking direction can however be easily changed by changing the position of the stop screw
- The lever distance can be variably adjusted by 1-5 mm depending on the installation location. Bending the lever is not necessary.

Product description

- Brass cylinder
- Standard finish, matt chrome-plated (OF=MC)
- Number of pin tumblers dependent on system
- Drilling protection (AB=), locking wave (SW=), additional lateral scanning, security card depending on profile (PR=)
- Spherical / Tapered cylinder core head with reinforced key guide
- Core pins made of special wear-resistant bronze
- Locking lever path 90°
- Two locking lever end positions
- Fixing with M30x1.5 housing nut
- Key rotation 360° (2 key retraction positions)
- Locking lever SLHB= 1647004 (other locking levers available on request)

Scope of delivery

- 1 locking lever cylinder
- 2 nickel silver keys
- 1 housing nut M30 x 1.5 x 4
- 1 installation kit 1915,AUS=SATZ 001 (2 locking core nuts M10 x 0.75 x 3, 5 shim 1 mm, 1 catchplate, 1 setscrew M2,5 x 10)

Note

- The lever distance can be variably adjusted by 1-5 mm depending on the installation location. Bending the lever is not necessary.

Ordering Information

- Not available with drilling protection 2 (AB=2) or 3 (AB=3)
- Please include the desired locking path (SST=) in your order.

Suitable ASSA ABLOY products

- Maintenance spray 8511
- Escutcheon with rain protection cover 1254,AUS=1

