



Overview of Advantages

- The locking direction of the locking lever can be given when ordering; the locking direction can however be easily changed by changing the position of the stop screw

Product description

- Brass cylinder matt chrome-plated
- Number of pin tumblers dependent on system
- Standard finish, matt chrome-plated (OF=MC)
- Locking wave (SW=), additional lateral scanning and security card depending on profile (PR=)
- Spherical / Tapered cylinder core head with reinforced key guide
- Core pins made of special wear-resistant bronze
- Locking path and locking lever path 90° left or right
- Key withdrawal when locking lever is closed
- Fixing with housing nut M23 x 0.75
- Standard locking lever (SLHB=1645009)
- Dimension a, b, c, d in mm dependent on system (L=)

Scope of delivery

- 1 locking lever cylinder
- 2 nickel silver keys
- 1 casing screw nut M23 x 0.75
- 1 core nut, M10 x 0,75 x 3

Ordering Information

- Please include the desired locking path (SST=) in your order.
- Cylinder length L= is necessary in your order for measurements a,b,c,d with L=25 (25, 35, 21, 16) or L=29 (29, 39, 25, 20)
- The actual lengths for a and b can deviate by +0.5 mm

Suitable ASSA ABLOY products

- Maintenance spray 8511
- Escutcheon with rain protection cover 1254,AUS=2-7