

Standard version

## Overview of Advantages

- The test winner in 2009 - now in improved performance and installation-friendly than ever!

## Product description

- Provides optimum protection against intrusion and levering open of the door on hinge and lock side
- Dual dead bolt system (DRS) - With two fully-extended dead bolts on each side for four-fold security
- Suitable for door widths from 600 to 1200 mm
- Solid hardened steel dead bolt
- Dead bolt 80 mm
- Freely-rotating dead bolt impedes tampering with tools
- 3-point anchoring of lock case with solid wall anchor
- Available in color: silver grey (FB=SGR) similar to RAL 9006, white (FB=WS) similar to RAL 9016 and brown (FB=BN) similar to RAL 8019
- The same locking direction as for the main lock can be achieved due to a simple conversion of the locking direction; suitable for DIN left and right applications
- Material: steel

## Scope of delivery

- 1 Protector bar with fixing material (without security escutcheon and cylinder)

## Note

- VdS approval only in combination with a security escutcheon and a VdS-A approved locking cylinder
- Profile cylinder not included

## Suitable ASSA ABLOY products

- Profile-double cylinder .531
- Profile-knob cylinder .534,KNF=1
- Profile-knob cylinder .534,KNF=2
- Profile-knob cylinder .534,KNF=7
- Profile-knob cylinder .534,KNF=9
- Profile-knob cylinder .534,KNF=91
- Profile-knob cylinder .534,KNF=92
- Spyhole 9M35

## Accessories/Individual parts

- Security escutcheon with cylinder cover 9M28
- Security escutcheon with cylinder cover S464
- Wall striking plate 8451
- Security link lock case 8450
- Mounting set DRS 8442

## Variants that can be ordered

Article number	FB=
8443 49082	SGR
8443 49083	WS
8443 49084	BN

