



Product description

- OneSystem sash lock N1050 according to EN 12209 for single-leaf standard doors/ approved for fire barriers according to EN 1634 / product-specific environmental product declaration (EPD) according to EN 15804 with article-specific parameters /tested for 1,000,000 cycles and 300 kg door weight

Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 17 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Closed lock case
- Latch DIN left/right reversible without tools
- Security fittings and oval roses can be screwed on through the lock
- Stainless steel faceplate
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Note

- Steel bolt only available for backset 65 and 100 mm. 55, 60 and 80 mm on request.

Technical data

Bolt throw	20 mm
Standards	EN 12209
Material faceplate	Stainless steel
Shape	R3 x 20 mm
Latch	DIN L
Stulp	R3 x 20 mm
Material striking plate	Stainless steel
Face plate length	235 mm
Mounting	Sash lock
Panic function	nein
door system	Single-leaf door
Backset	55 mm
Handing	DIN L
Suitable for fire doors	Yes
Obenverriegelung	No
Self-locking system	No
Type of cylinder	Swiss profile cylinder
Handle follower	9 mm
Distance	74 mm
Monitoring	No
Symmetry	asymmetrical

Article number	N1050201981000M
EAN-Number	4042203490802