



Product description

- OneSystem bathroom lock N1001 for single-leaf standard doors, product-specific environmental product declaration (EPD) in accordance with EN 15804 with article-specific Parameters.

Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 17 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Closed lock case
- Latch DIN left/right reversible without tools
- Security fittings and oval roses can be screwed on through the lock
- Stainless steel faceplate
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Note

- Steel bolt only available for backset 65 and 100 mm. 55, 60 and 80 mm on request.

Technical data

Bolt throw	20 mm
Standards	EN 12209
Material faceplate	Stainless steel
Latch	DIN R
Stulp	R3 x 20 mm
Material striking plate	Stainless steel
Face plate length	235 mm
Width face plate	20 mm
Mounting	Bathroom lock
Panic function	nein
door system	Single-leaf door
Backset	80 mm
Handing	DIN R
Suitable for fire doors	No
Obenverriegelung	No
Self-locking system	No
Function	mechanisch
Type of cylinder	no cylinder cutout
Handle follower	8 mm
Distance	78 mm
Monitoring	No
Shape	round
Symmetry	asymmetrical

Article number	N10013028B5000M
EAN-Number	4042203569898