



### Product description

- OneSystem roller bolt lock N1510 for single-leaf doors, product-specific environmental product declaration (EPD) in accordance with EN 15804 with article-specific parameters.

### Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 15 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Latch DIN left/right reversible without tools
- Closed lock case at the top and bottom
- Stainless steel faceplate
- Security fittings and oval roses can be screwed on through the lock
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

### Technical data

Latch	DIN L/R
Stulp	F3 x 20 mm
Material striking plate	Stainless steel
Face plate length	270 mm
Mounting	Roller latch deadbolt lock
Panic function	nein
door system	Single-leaf door
Material faceplate	Stainless steel
Bolt throw	20 mm
Standards	EN 12209
Backset	40 mm
Handing	DIN L/R
Suitable for fire doors	No
Obenverriegelung	No
Self-locking system	No
Type of cylinder	Profile cylinder
Distance	92 mm
Monitoring	No
Shape	square, flat
Symmetry	symmetrical

Article number

N15100008530009

EAN-Number

4042203473270

