



Product description

- OneSystem roller bolt lock N1510 for single-leaf doors, product-specific environmental product declaration (EPD) in accordance with EN 15804 with article-specific parameters.

Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 15 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Latch DIN left/right reversible without tools
- Closed lock case at the top and bottom
- Stainless steel faceplate
- Security fittings and oval roses can be screwed on through the lock
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Technical data

Latch	DIN L/R
Monitoring	No
Symmetry	symmetrical
Self-locking system	No
Distance	92 mm
Stulp	U6 x 24 mm
Type of cylinder	Profile cylinder
Suitable for fire doors	No
Face plate length	320 mm
Mounting	Mortise roller bolt lock
Panic function	nein
Top locking	No
door system	Single-leaf door
Backset	25, 30, 35, 40, 45 mm
Material faceplate	Stainless steel
Bolt throw	20 mm
Handle follower	8 mm
Standards	EN 12209
Shape	U6 x 24 mm

Variants that can be ordered

Order number	Backset
N1510000850000F	25 mm
N1510000851000F	30 mm
N1510000852000F	35 mm
N1510000853000F	40 mm
N1510000854000F	45 mm