



Product description

- OneSystem latch lock N1502 for single-leaf doors, product-specific environmental product declaration (EPD) in accordance with EN 15804 with article-specific Parameters.

Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 15 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Latch DIN left/right reversible without tools
- Closed lock case at the top and bottom
- Stainless steel faceplate
- Security fittings and oval roses can be screwed on through the lock
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Technical data

| | |
|-------------------------|--------------------|
| Latch | DIN L/R |
| Distance | no distance |
| Stulp | R3 x 20 mm |
| Type of cylinder | no cylinder cutout |
| Material striking plate | Stainless steel |
| Face plate length | 185 mm |
| Mounting | Mortise latch |
| Panic function | nein |
| door system | Single-leaf door |
| Material faceplate | Stainless steel |
| Bolt throw | 20 mm |
| Standards | EN 12209 |
| Backset | 25 mm |
| Handing | DIN L/R |
| Suitable for fire doors | No |
| Top locking | No |
| Self-locking system | No |
| Handle follower | 8 mm |
| Monitoring | No |
| Symmetry | symmetrical |
| Article number | N15020008X0001B |
| EAN-Number | 4042203577244 |