



Product description

- OneSystem espagnolette N1910 for automatic locking of the inactive leaf upwards or downwards for double-leaf doors. For use with OneSystem locks from the series N1050, N155X, N16XX and N7XXX (N16XX and N7XXX only for partial panic) on the active leaf of bi-parting profile doors.

Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 15 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Latch DIN left/right reversible without tools
- Closed lock case at the top and bottom
- Stainless steel faceplate
- Security fittings and oval roses can be screwed on through the lock
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Technical data

Distance	92 mm
Stulp	F3 x 24 mm
Face plate length	320 mm
Mounting	Inactive leaf locking system
Backset	30, 35, 40, 45 mm
Material faceplate	Stainless steel
Latch	DIN L/R (symmetrical face plate)

Variants that can be ordered

Order number	Backset
N1910000XX1000E	30 mm
N1910000XX2000E	35 mm
N1910000XX3000E	40 mm
N1910000XX4000E	45 mm

