



Product description

- OneSystem sash lock N1050 according to EN 12209 for single-leaf standard doors/ approved for fire barriers according to EN 1634 / product-specific environmental product declaration (EPD) according to EN 15804 with article-specific parameters /tested for 1,000,000 cycles and 300 kg door weight

Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 17 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Closed lock case
- Latch DIN left/right reversible without tools
- Security fittings and oval roses can be screwed on through the lock
- Stainless steel faceplate
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Note

- Steel bolt only available for backset 65 and 100 mm. 55, 60 and 80 mm on request.

Technical data

Bolt throw	20 mm
Standards	EN 12209
Backset	55, 60, 65, 80, 100 mm
Material faceplate	Stainless steel
Shape	R3 x 20 mm
Latch	DIN L/R
Monitoring	No
Symmetry	symmetrical
Self-locking system	No
Distance	distance 72 mm
Handing	DIN L/R
Handle follower	9 mm
Stulp	R3 x 20 mm
Type of cylinder	Profile cylinder
Suitable for fire doors	Yes
Mounting	Sash lock
Panic function	nein
Top locking	No
door system	Single-leaf door
Face plate length	235 mm

Variants that can be ordered

Order number	Backset
N1050000911000L	55 mm
N1050000912000L	60 mm
N1050000913000L	65 mm
N1050000915000L	80 mm
N1050000917000L	100 mm