



### Product description

- OneSystem latch lock N1002 for single-leaf standard doors, product-specific environmental product declaration (EPD) in accordance with EN 15804 with article-specific Parameters.

### Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 17 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Closed lock case
- Latch DIN left/right reversible without tools
- Security fittings and oval roses can be screwed on through the lock
- Stainless steel faceplate
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

### Technical data

Bolt throw	20 mm
Latch	DIN L
Standards	EN 12209
Distance	no distance
Stulp	R3 x 20 mm
Type of cylinder	no cylinder cutout
Material striking plate	Stainless steel
Material faceplate	Stainless steel
Face plate length	185 mm
Width face plate	20 mm
Mounting	Mortise latch
Panic function	nein
door system	Single-leaf door
Backset	65 mm
Handing	DIN L
Suitable for fire doors	No
Top locking	No
Self-locking system	No
Function	mechanisch
Handle follower	8 mm
Monitoring	No
Shape	round
Symmetry	asymmetrical
Article number	N10022008X3001E
EAN-Number	4042203577152