

OneSystem standard project lock wide stile

ASSA ABLOY



Product description

- OneSystem espagnolette N1410 for automatic locking of the inactive leaf upwards or downwards for double-leaf doors. For use with OneSystem locks from the series N1000, N105X and N11XX (N11XX only for partial panic) on the active leaf of bi-parting profile doors.

Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 17 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Closed lock case
- Latch DIN left/right reversible without tools
- Security fittings and oval roses can be screwed on through the lock
- Stainless steel faceplate
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Technical data

| | |
|--------------------|----------------------------------|
| Bolt throw | 20 mm |
| Standards | EN 12209 |
| Handle follower | 8 mm |
| Material faceplate | Stainless steel |
| Latch | DIN L/R (symmetrical face plate) |
| Distance | 74 mm |
| Stulp | F3 x 24 mm |
| Face plate length | 235 mm |
| Mounting | Inactive leaf locking system |
| Backset | 80 mm |

| | |
|----------------|-----------------|
| Article number | N1410000XX50006 |
|----------------|-----------------|

