

OneSystem standard project lock wide stile

ASSA ABLOY



Product description

- OneSystem espagnolette N1410 for automatic locking of the inactive leaf upwards or downwards for double-leaf doors. For use with OneSystem locks from the series N1000, N105X and N11XX (N11XX only for partial panic) on the active leaf of bi-parting profile doors.

Overview of Advantages

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 17 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Closed lock case
- Latch DIN left/right reversible without tools
- Security fittings and oval roses can be screwed on through the lock
- Stainless steel faceplate
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Technical data

Bolt throw	20 mm
Standards	EN 12209
Handle follower	8 mm
Material faceplate	Stainless steel
Latch	DIN L/R (symmetrical face plate)
Distance	74 mm
Stulp	R3 x 20 mm
Face plate length	235 mm
Mounting	Inactive leaf locking system
Backset	65 mm

Article number	N1410000XX30001
----------------	-----------------

